



Adsorbent Solutions, LLC

7100 St. Gabriel Ave

St. Gabriel, LA 70776

AG-900, AG-1000

AG-900, AG-1000 activated carbon is a virgin activated carbon. Produced from bituminous coal. It is granular in form. It's ideal for many liquid phase applications including the removal of organics from water streams. It's a superior adsorptive capacity and surface area make it particularly attractive for use with potable water while its size make it appealing where low-pressure drop is needed.

Specification:

Mesh Size:	6x10, 6x12, 8x16, 8x20, 8x30, 12x40, 4x10	
Ash(wt%):	18 Max.	D2866-94
Moisture:	3% Max.	D28267-91
Hardness No:	90 Min.	D3802-79
Iodine No:	900Mg/g Min.	D4607-94
Density:	.45-.52 g.ml	D2854-94
Abrasion:	80 Min.	B604

Packaging:

Material is to be packed in black super sacks with 500KG or 1100 Lb. net each, 2 super sacks per pallet. 20-25 KG small bags are available.

Remarks:

The above specification can be adjusted in accordance with the customer's requirement.

Cell: 713-899-8269

Office: 225-319-7130

Fax: 225-208-1860

Email: stewart@adsorbentsolutions.com

www.adsorbentsolutions.com